

Digital SWR / Watt Meter

Model: MFJ-849 Operation manual

INTRODUCTION

This digital SWR & Watt meter is highly accurate for measuring Forward Power, Reflected Power, & VSWR.

Main Features:

- 1. Large LCD (3.5") display for easy of reading.
- 2. Forward / Reflected power / VSWR ratio in one push button.
- 3. LCD backlight display.
- 4. Convenient control layout for easy operation
- 5. Packing gift box and DC 12V wire.

SPECIFICATIONS

MODEL	MFJ-849
Frequency Range	1.6-60 MHz / 125-525 MHz
Caibration point	14MHz / 50MHz / 145MHz / 435MHz
Power Range	0 - 200W
Ассыгасу	(+/- 5%)
Minimum Power for SWR	1W
Input/Output Connector	SO239
Weight (Net)	750 g
Insertion Loss	Less than 0.1 dB
Testing Function	Fwd/Ref Power & VSWR ratio
Input/Output Impedance	50 Ohm
Dimension (W/H/D) mm	140 x 84 x 122
Accessories	Operation Manual, 12V DC Wire


<FRONT PANEL>



<FRONT & REAR PANEL>

- 1. LCD Display: Indicates FWD/REF and VSWR
- 2. HF & V/UHF band switch.
- 3. Power switch

<REAR PANEL>



<REAR PANEL>

5.TX connector: Coax connector to transmitter RF output 6. ANT connector: Coax connector to antenna system

7. Power source :13.8V DC wire